

# Multi-Region Active-Active Agent Platforms: Architecting for Regional Sovereignty, Global State, and Deterministic Failover

## 1. Contextual Foundations and Architectural Assumptions

The transition from localized, single-region agent deployments to a globally distributed, active-active platform represents a profound shift in distributed systems engineering. The design of such a platform does not occur in a vacuum; it builds upon a robust foundation of existing architectural paradigms. Prior research and implementations have firmly established a baseline that must serve as the incontrovertible starting point for this global expansion. The existing programme operates upon an internal canonical task architecture, utilizing formalized handoff protocols, tool-intent verifications, tool-receipt logs, and a rigorous event-based state machine. Crucially, external Agent-to-Agent (A2A) protocols are strictly designated as gateway communication layers. These external protocols must be deterministically translated into the internal canonical task model rather than being permitted to dictate or become the platform's authoritative state machine. The architecture enforces a rigid separation between the control plane and the execution plane, ensuring that the orchestration of workflows is decoupled from the inherently untrusted execution of stochastic agent workloads.

Furthermore, the existing infrastructure relies on mature registries for projects, fleets, providers, environments, and agents. Security is enforced through workload identity, just-in-time credentials, specialized credential brokers, and tool proxies, with all untrusted workloads running within hardware-isolated execution environments. Policy-as-code and deterministic authority enforcement govern all actions, backed by an event-first recovery model. This model utilizes bitemporal state tracking and immutable ledgers, ensuring safe, auditable workflow upgrades. Release pipelines demand cryptographically signed release evidence, Software Bills of Materials (SBOMs), and immutable artifact promotion via progressive delivery mechanisms. Ultimately, the system recognizes that stochastic models cannot authorize themselves; thus, human approval remains the current boundary for production deployments, and human attention constraints—specifically integration and review capacity—are acknowledged as the primary bottlenecks in the autonomous factory pipeline. Finally, project isolation, data residency compliance, and privacy-aware provider routing are heavily enforced at the platform boundary.

These established architectures are not subject to revision. Instead, they serve as the

foundational constraints upon which the multi-region active-active topology must be constructed.

## **2. Programme-Wide Architectural Principles**

The expansion into a multi-region architecture must strictly adhere to a set of core principles that govern the interaction between deterministic platform governance and stochastic agent execution.

### **2.1 The Uncompromising Authority of Internal State**

A fundamental axiom of the platform is that internal state remains absolute and authoritative. A remote agent's task status, natural language explanations, claimed completion rates, internal reputation scores, or ephemeral provider sessions must never directly mutate the authoritative internal ledger.

To maintain this isolation, all external communications must undergo a rigorous translation process into strict internal objects. When an external agent communicates with the platform, its payload is deserialized and mapped to internal representations such as `ExternalTaskOffer`, `RemoteTaskContract`, `ExternalAgentIdentity`, `DelegationGrant`, `ExternalEvidenceReceipt`, `RemoteArtifactReference`, `FederationPolicyDecision`, and `ExternalCompletionClaim`.

Consequently, an external completion claim generated by an agent does not represent a completed task; rather, it enters the internal platform strictly as evidence awaiting deterministic validation. Only after the control plane validates this evidence against human-defined policies does the internal state advance.

### **2.2 External Agents as Untrusted Service Providers**

The current A2A 1.0 family of standards defines Agent Cards, task lifecycles, structured content formats, streaming protocols, and asynchronous notification patterns. While it leverages standard transport-layer authentication and server-side authorization, protocol compliance must never be misconstrued as an attestation of trustworthiness.

The architecture dictates that protocol compliance is not proof that an agent actually possesses its advertised competence, nor does it guarantee that the agent handles data according to its claimed privacy policy. Compliance does not ensure the agent will remain available, resist prompt-injection attacks<sup>1</sup>, generate authentic cryptographic evidence, respect financial budgets or execution deadlines, or avoid catastrophic recursive delegation. External agents remain legally and financially unaccountable stochastic engines. As explicitly warned in official A2A samples, all remote Agent Cards, incoming messages, generated artifacts, and status records must be processed defensively as untrusted input.

### **2.3 Human Governance Over Stochastic Execution**

The removal of mandatory human approval for every granular action does not equate to the removal of human governance. For production deployments, the target authorization model requires that human-defined policy authorizes a bounded class of deployment. Deterministic platform controllers subsequently evaluate each stochastic release or agent action against this

rigid policy. While agents possess the capability to propose solutions, iterate on tasks, and initiate workflows, they are fundamentally barred from authorizing themselves. Humans explicitly retain absolute authority over the creation and modification of policy. This includes defining the maximum permissible blast radius for any agent, whitelisting permitted code repositories and deployment environments, and setting hard financial ceilings. Furthermore, human governance defines risk classes, dictates mandatory rollback requirements, initiates emergency stops and revocation protocols, and holds the sole authority to accept residual risks. This paradigm preserves the ironclad rule that stochastic, probabilistically driven Large Language Models (LLMs) cannot become the root of production authority.

## **2.4 Regional Independence and Cellular Topology**

In a global distributed system, regional independence must be prioritized over global coupling. The architecture mandates that each geographic region or logical cell must continue safe, uninterrupted local operation even when global orchestration services suffer total impairment. A global dependency is permissible only where globally consistent authority is mathematically necessary—such as global identity root distribution or absolute financial quota ceilings. All other operations must rely on regional ownership, asynchronous event replication, and deterministic reconciliation loops. The system must tolerate bounded staleness for global reads and seamlessly transition into read-only degraded modes when global consensus cannot be achieved, ensuring that the localized execution plane remains highly available.

## **2.5 Scale Through Ephemeral Execution**

The platform must scale to support thousands of concurrent projects without a linear explosion in permanent infrastructure. The existence of thousands of registered projects must not necessitate thousands of permanently running agent processes, dedicated Kubernetes clusters, or isolated database instances.

The architectural target clearly distinguishes between the state of a project and its compute requirements. The system tracks registered projects, enabled projects, and projects with currently queued work, but only allocates physical resources to concurrently active workflows, active agent execution attempts, and active sandboxes. Persistent logical identity and configuration state are stored inexpensively in high-density multi-tenant databases. Conversely, heavy compute resources, LLM model sessions, just-in-time credentials, and execution sandboxes remain strictly ephemeral, pooled, and dynamically provisioned based on instantaneous demand.

## **2.6 Measurable Evidence for Autonomous Expansion**

Every advancement in agent autonomy or geographic scale tier must be preceded by measurable, empirical evidence. The architecture prohibits blind expansion. Each new tier requires a formal update to the threat model, successful execution of deterministic conformance tests, and survival against adversarial scenarios and failure-injection tests. Capacity tests, automated recovery drills, and rigorous economic modeling must be

completed. Only upon the demonstration of sustained, fault-tolerant operational evidence can the platform's boundaries be extended.

### 3. The Multi-Region Active-Active Challenge: Simultaneous Authority

The core challenge of establishing a globally distributed agent platform lies in enabling multiple geographic regions to simultaneously accept projects, schedule agent workloads, and execute tasks without generating catastrophic split-brain scenarios. The system must prevent duplicated external side effects, ensure consistent policy approvals, and rigorously enforce cross-region data-residency violations.

#### 3.1 Divergence from Disaster Recovery

It is critical to distinguish an active-active architecture from traditional disaster recovery (DR). Existing DR architectures rely on an immutable event ledger and asynchronous replication. In a DR scenario, a secondary region maintains rebuildable projections and bitemporal corrections; if the primary fails, a reconciliation loop activates a safe-mode recovery protocol, eventually elevating the secondary to primary status.

Active-active architectures, however, grapple with the profound complexities of simultaneous authority. Modern multi-region databases and distributed consensus protocols demonstrate that true active-active execution requires explicit, mathematically sound decisions regarding which region owns a specific task, where transactional writes are permitted to occur, how workflows safely migrate across boundaries, and how execution leases are fenced. It also dictates stringent rules for data replication, the maintenance of global quotas under partition, and the deterministic reconciliation of conflicting regional actions.

#### 3.2 Evaluating Regional Topologies

A comprehensive comparison of distributed topologies is required to determine the optimal structure for the agent platform.

| Topology Model               | Architectural Characteristics                                         | Viability for Agent Platform                                                                 |
|------------------------------|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| Active-Passive Control Plane | Single global writer, asynchronous replication to a warm standby.     | Rejected. High WAN latency for global agents; total failure during control plane partitions. |
| Warm-Standby Region          | Infrastructure is provisioned but inactive until manual or DNS-driven | Rejected. Wastes massive compute resources; RTO (Recovery Time Objective)                    |

|                                                   |                                                                                                                                           |                                                                                                                                                                                                                                                                                              |
|---------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                   | failover.                                                                                                                                 | is too high for continuous agent loops.                                                                                                                                                                                                                                                      |
| <b>Active-Active API (Single-Writer Workflow)</b> | Global API accepts requests anywhere, but a specific workflow is pinned to a single global database master.                               | Insufficient. Creates a massive database bottleneck and exposes workflows to cross-region database latency <sup>2</sup> .                                                                                                                                                                    |
| <b>Globally Replicated Consensus</b>              | Distributed consensus protocols (e.g., EPaxos, WPaxos) allow multi-leader commits across a Wide Area Network (WAN).                       | Rejected for primary execution. While WPaxos dynamically partitions object-space and uses flexible quorums to reduce latency (achieving up to 18x faster commits than EPaxos) <sup>3</sup> , global consensus for every micro-task is economically and computationally prohibitive at scale. |
| <b>Independent Sovereign Regions (Federated)</b>  | Entirely disconnected deployments communicating only via asynchronous federation.                                                         | Sub-optimal. Fails to provide a unified organizational view, global budget enforcement, or seamless project migration.                                                                                                                                                                       |
| <b>Target: Active-Active Regional Cells</b>       | Global governance for discovery and policy. Explicit home-region ownership for projects. Immutable cross-region asynchronous replication. | <b>Preferred.</b> Eliminates uncontrolled multi-master workflow mutations while localizing execution latency to the cell <sup>5</sup> .                                                                                                                                                      |

The target architecture utilizes Global governance and discovery paired with regional project ownership. Execution is strictly cell-local, relying on immutable cross-region event replication and explicit, cryptographic ownership transfer to prevent uncoordinated multi-master workflow mutation.

### 3.3 State Classification by Consistency Requirement

Applying a universal strong consistency model across a global network violates the CAP

theorem and results in unacceptable latency. Therefore, the architecture categorizes state domains by their explicit consistency tolerances.

| State Type               | Consistency Requirement & Implementation Strategy                                                                                                                                |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval and Authority   | <b>Strongly consistent or home-region authoritative.</b> Requires distributed locks or linearizable transactions (e.g., CockroachDB serializable isolation) <sup>6</sup> .       |
| Task Ownership & Fencing | <b>Strongly consistent within the ownership domain.</b> Validated at the resource level via monotonic fencing tokens <sup>8</sup> .                                              |
| Workflow History         | <b>Ordered authoritative stream.</b> Append-only within the home cell, replicated asynchronously with causal ordering guaranteed by Hybrid Logical Clocks (HLCs) <sup>10</sup> . |
| Audit Events             | <b>Asynchronously replicated.</b> Eventual consistency is acceptable; requires exactly-once delivery semantics via transactional outboxes <sup>12</sup> .                        |
| Project Configuration    | <b>Versioned and convergent.</b> Configuration changes replicate globally but execute locally based on the highest cryptographic version seal.                                   |
| Provider Pricing         | <b>Eventually consistent.</b> Pricing updates propagate with effective timestamps to allow cells to calculate budgets locally <sup>13</sup> .                                    |
| Global Dashboards        | <b>Stale-tolerant projection.</b> Derived from asynchronous event streams; heavily optimized for fast, eventually consistent reads.                                              |
| Emergency Kill State     | <b>Strong, independently propagated.</b> Must                                                                                                                                    |

|  |                                                                                                                                            |
|--|--------------------------------------------------------------------------------------------------------------------------------------------|
|  | bypass standard queues, utilizing out-of-band propagation (e.g., AWS SNS cross-region delivery) to halt execution globally <sup>14</sup> . |
|--|--------------------------------------------------------------------------------------------------------------------------------------------|

### 3.4 Project Placement and Data Residency Constraints

The platform must navigate stringent legal requirements regarding data sovereignty, particularly the European Union's General Data Protection Regulation (GDPR). GDPR Article 44 prohibits the transfer of personal data outside the EU/EEA unless the recipient country is deemed to have adequate data protection, or appropriate safeguards (such as Standard Contractual Clauses with Transfer Impact Assessments) are enforced<sup>16</sup>.

To enforce this, the architecture defines a `ProjectPlacementPolicy` schema. This schema explicitly defines the project's home region, a whitelist of permitted execution and failover regions, the strict data-residency zone, control-plane ownership, memory location constraints, artifact replication boundaries, provider eligibility, failover modes, and maximum accepted staleness.

In the event of a regional outage, the platform is strictly mandated to **fail closed** if no compliant region is available<sup>18</sup>. A project containing restricted EU data must never silently fail over to a non-EEA region, as mere remote access or cross-border cloud storage constitutes an unauthorized international data transfer under GDPR, exposing the organization to catastrophic regulatory fines (e.g., up to 4% of global turnover)<sup>18</sup>. Residency constraints are evaluated deterministically at the task-admission boundary.

### 3.5 Regional Cell Encapsulation

The fundamental building block of the execution plane is the regional cell. A cell operates as an independently survivable unit that isolates failures and prevents cascading global outages. Each cell encompasses a highly specialized suite of components. It relies on a local task-admission partition to ingest and validate incoming workloads against the `ProjectPlacementPolicy`. A dedicated cellular scheduler distributes tasks to localized workflow workers and an ephemeral execution-worker pool. The cell maintains its own model gateways and tool gateways to intermediate external API calls, ensuring that rate limits and circuit breakers are enforced locally. Furthermore, each cell operates a regional event-ingestion service, a localized projection of project state, an independent caching layer, and an observability collector that buffers telemetry during network partitions. Crucially, each cell includes an emergency containment control system capable of severing all external agent communication instantly.

To guarantee survivability, cells possess bounded project membership and a mathematically calculated maximum blast radius. They maintain independent capacity reserves and rely on local circuit breakers to shed load during provider outages. Routine execution within one cell holds absolutely no synchronous dependence on the availability of any other cell on the global network.

## 3.6 Global Services and Degraded Operation

While execution is localized, certain coordination mechanisms inherently require global context. The architecture defines a strict subset of services that operate globally: the organization and project directory, the cell-placement directory, the global policy catalogue, publisher trust roots, the overarching schema registry, global budget allocation, cross-region audit indexes, federation registries, and global emergency authority mechanisms.

Because global consensus incurs significant latency and vulnerability to WAN partitions, every global service is engineered to support degraded regional operation. If a regional cell loses connectivity to the global policy catalogue, it must not halt execution. Instead, the cell's admission controller falls back to the most recently verified, cryptographically signed policy cache, rejecting any tasks that require un-cached or dynamically evaluated global permissions until connectivity is restored.

## 4. Defeating Split-Brain: Fencing, Leases, and Idempotency

The most severe risk in an active-active distributed system is the duplication of external side effects. If a region goes offline, a standby region may take over a workflow. However, if the primary region was merely experiencing a transient network partition or a severe garbage collection (GC) pause, it may eventually resume operation. Without rigorous mathematical controls, both regions will simultaneously believe they hold authority, resulting in a split-brain scenario where an agent executes a financial transaction or sends a critical email twice.

### 4.1 The Insufficiency of Simple Leases

Standard distributed locks, even those utilizing expirations (leases), are insufficient to guarantee correctness. The Redlock algorithm, implemented over Redis, attempts to provide fault-tolerant distributed locking by requiring a quorum of nodes to grant a lease<sup>20</sup>. However, as thoroughly demonstrated by distributed systems researchers like Martin Kleppmann, a time-bound lease only protects the *lock service* from deadlocks; it provides zero protection to the *target resource* if the client holding the lease experiences a pause<sup>9</sup>.

Consider a worker agent in Region A that acquires a 10-second lease to process a payment. Two seconds into execution, the worker's runtime environment initiates a 12-second stop-the-world GC pause. The lock service observes the lease expire and legitimately grants a new lease for the same task to a worker in Region B. Region B successfully processes the payment. Subsequently, Region A finishes its GC pause. Because it believes its initial lease is still valid (having been suspended in time), it also transmits the payment request. The result is a corrupted state and a duplicated financial charge<sup>9</sup>.

### 4.2 Resource-Level Enforcement via Monotonic Fencing Tokens


To achieve absolute safety and prevent cross-region approval replay, the architecture mandates a three-party protocol utilizing monotonic fencing tokens.

Under this protocol, the lock service does not merely grant a binary lease; it issues a monotonically increasing integer (the fencing token) generated by a consensus-backed consistent core (e.g., etcd, ZooKeeper, or CockroachDB transaction records) every time a lease is granted<sup>8</sup>.

The worker must append this fencing token to every mutation request sent to the storage layer or tool gateway. The critical shift in this architecture is that the target resource takes an active role in enforcing mutual exclusion. The resource tracks the highest token it has ever observed for a given entity. If a write request arrives bearing a token lower than the highest recorded token, the resource deterministically rejects the operation<sup>22</sup>.

Returning to the previous scenario: Region A acquires the lease and receives Token 33. Region A pauses. Region B acquires the lease and receives Token 34. Region B successfully executes the write, and the resource records Token 34 as the high-water mark. When Region A wakes up and attempts to write using Token 33, the resource rejects the write because 33 is strictly less than 34. The stale worker is fenced out, and the dual-execution incident is neutralized<sup>9</sup>.

# Preventing Split-Brain Execution via Monotonic Fencing Tokens



A distributed lease protects the lock service from deadlocks, but only a fencing token validated at the resource layer can protect the system from delayed, split-brain writes caused by garbage collection pauses or network partitions.

Data sources: [Martin Kleppmann](#), [AppScale Blog](#), [LevelUp](#)

## 4.3 Idempotency and External Side Effects

While fencing tokens protect the internal state machine, agents frequently interact with external, third-party APIs that do not support custom token validation. To ensure these external side effects are not duplicated, the architecture heavily leverages engineered idempotency<sup>26</sup>. An idempotency key, typically a UUID scoped to the specific client and operation intent, guarantees that executing an operation multiple times yields the same intended effect as executing it once<sup>26</sup>. However, generating a key is insufficient if the system crashes mid-operation. The architecture implements the **transactional outbox pattern** to resolve this. When an agent initiates a side effect, the platform reserves the idempotency key, executes the local state update, and writes the outgoing event to an outbox table—all within a single, atomic database transaction<sup>12</sup>. A background poller then reliably publishes the event to the external provider. If the system crashes after the API call but before recording the response, the unique

constraint on the idempotency key in the database ensures that a retried request will recover the state rather than initiating a duplicate charge<sup>12</sup>.

## **5. Event Replication, State Causal Ordering, and Concurrency**

To support active-active failovers, workflow history cannot exist in isolation. However, synchronous dual-writes—where a worker attempts to write to both Region A and Region B simultaneously—are banned due to their catastrophic impact on latency and their vulnerability to distributed deadlocks<sup>5</sup>.

### **5.1 Multi-Cluster Replication and Conflict Resolution**

The platform utilizes an asynchronous multi-cluster replication architecture, akin to the underlying engine of Temporal. Workflows are processed in an active cluster, and their execution histories are asynchronously replicated to passive standby clusters to facilitate state reconstruction<sup>29</sup>.

Because replication is asynchronous, cross-cluster data is not strongly consistent in real-time. To ensure eventual consistency during a regional failover, the system relies on Namespace Versions. Every workflow history entry generated within a namespace is stamped with a version integer specific to that cluster<sup>29</sup>. All participating clusters are pre-configured with a unique initial version and a shared version increment (e.g., Cluster A starts at 1, Cluster B starts at 2, incrementing by 10)<sup>29</sup>.

If a network partition causes a split-brain scenario where both clusters temporarily accept writes for the same workflow, a data conflict occurs upon reconnection. The conflict resolution algorithm compares the divergent execution histories; the history branch carrying the highest namespace version is deterministically declared the source of truth, and the divergent branch is safely discarded or logged as a zombie workflow<sup>29</sup>.

### **5.2 Workflow Migration and Continue-As-New**

For prolonged autonomous operations, workflow event histories can grow excessively large, degrading performance as workers must constantly replay history to rebuild state upon cache misses<sup>31</sup>.

To safely rehome long-running workflows across regions or to manage excessive event histories, the platform utilizes a Continue-As-New mechanism. This protocol checkpoints the workflow's current state, safely terminates the execution in the source region, and instantly passes the state payload to a fresh workflow execution in the target region. The new execution retains the original Workflow ID but begins with a clean Event History and a new Run ID, ensuring seamless migration without violating linearizability<sup>31</sup>.

### **5.3 Hybrid Logical Clocks (HLCs) and Global Serialization**

Establishing a causal order of events across regions without a single global database master requires highly synchronized timekeeping. Relying purely on physical wall-clocks is disastrous

due to NTP synchronization delays and clock drift.

Systems like Google Spanner solve this utilizing TrueTime, which depends on physical GPS receivers and atomic clocks to provide a strictly bounded uncertainty interval (epsilon)<sup>13</sup>.

Because the agent platform operates across disparate cloud providers and commodity hardware, it implements Hybrid Logical Clocks (HLCs).

HLCs combine physical time with a logical counter, providing a mechanism to generate monotonically increasing timestamps that capture causal relationships across distributed nodes<sup>10</sup>. Distributed transactional databases underpinning the platform (such as CockroachDB) utilize HLCs to enforce Serializable isolation. When a write occurs, the HLC timestamp is checked against a cache. If the node detects that its physical clock is out of sync with the cluster majority by a maximum configured offset, the node deliberately crashes itself to preserve single-key linearizability and prevent write skew anomalies<sup>36</sup>. This ensures that cross-region event ledgers remain mathematically provable and consistently ordered.

## **6. Global Scheduling, Latency Mitigation, and Network Routing**

Attempting to route every granular agent task through a central global scheduler introduces profound latency bottlenecks dictated by the speed of light. Network physics cannot be circumvented; while intra-Availability Zone latency sits at roughly 0.44 milliseconds, a cross-region request from US-East to Europe averages 90-100 milliseconds, and to Asia Pacific can exceed 250 milliseconds<sup>38</sup>. A global scheduler enforcing synchronous limits on high-frequency stochastic loops would throttle the execution plane to a halt.

### **6.1 Hierarchical Quota Leasing**


To enforce organization-wide budgets, provider rate limits, and concurrent sandbox executions without synchronous chokepoints, the platform employs a hierarchical token-bucket scheduling model<sup>41</sup>.

1. A global budget allocation service holds the master organizational limits.
2. The global service asynchronously leases blocks of quota (tokens) to the individual regional cells based on historical utilization and routing policies.
3. The regional cell's local scheduler consumes tokens from its localized bucket for every task admission and model invocation, achieving microsecond latency.
4. Periodic background reconciliation loops sync the consumed metrics back to the global service.


If a cell exhausts its leased quota, it must pause admissions and asynchronously request a token replenishment from the global plane. If the global plane is unreachable due to a partition, the cell continues operating strictly up to the limit of its current lease, preventing budget overruns while maintaining safe local liveness.

# Network Physics vs. Execution Autonomy: Justifying Regional Quota Leases

AWS Inter-Region Network Latency (RTT)



Hierarchical Token Bucket: Regional Quota Leases



Because inter-region round-trip times (top) introduce unacceptable delays for stochastic agent loops, the platform avoids synchronous global coordination. Instead, global budgets are periodically leased to regional token buckets (bottom), allowing cells to schedule work locally at high speed.

Data sources: [Bits and Cloud](#), [Cloudping](#), [arXiv \(Token Bucket Routing\)](#).

## 6.2 Intelligent Anycast Routing and Health Checks

Relying on traditional DNS updates for failover is severely flawed due to variable client-side TTL

caching, resulting in prolonged downtime during regional shifts. To ensure deterministic, sub-second regional failover, the platform ingress utilizes technologies analogous to AWS Global Accelerator<sup>42</sup>.

Global Accelerator provisions static Anycast IP addresses, onboarding traffic at the edge location geographically closest to the originating agent or client, and routing it over an optimized private backbone to lower first-byte latency and jitter<sup>42</sup>. Crucially, the accelerator performs continuous TCP/HTTP health checks against the regional endpoints. If a regional cell's ingress controller fails a health check threshold (e.g., consecutive failures over a 10-second interval), the accelerator instantaneously removes the endpoint and shifts all incoming global traffic to the next optimal healthy region<sup>44</sup>. This mechanism decouples external endpoint resolution from internal database health, ensuring that a dying region stops accepting tasks before it corrupts state.

## 7. Multi-Region Identity Federation and Workload Secrets

Global identity management for ephemeral execution sandboxes presents a unique challenge: centralizing identity creation creates a massive single point of failure, while entirely disjointed regional identities prevent agents from verifying cross-region claims. The architecture leverages the SPIFFE (Secure Production Identity Framework for Everyone) standard and its reference implementation, SPIRE, to solve this<sup>47</sup>.

### 7.1 SPIRE Architectures: Nested vs. Federated

To establish cryptographic workload identity that transcends geographic boundaries without sharing private keys, the platform relies on two distinct SPIRE deployment topologies:

| SPIRE Topology          | Mechanism                                                                                                                                                                                                     | Architectural Use Case                                                                                                                                                                                                    |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Nested SPIRE</b>     | Downstream (regional) SPIRE servers are "chained" to an upstream (global) server. The regional server authenticates via the Workload API to obtain an intermediate Certificate Authority (CA) <sup>47</sup> . | Ideal for a single organizational boundary spanning multiple regions. If the global server crashes, regional servers continue issuing SVIDs using their valid intermediate CAs, providing high resilience <sup>48</sup> . |
| <b>SPIRE Federation</b> | Distinct Trust Domains (e.g., <code>spiffe://eu.platform.local</code> and <code>spiffe://us.platform.local</code> )                                                                                           | Necessary when integrating untrusted external agent fleets or third-party providers. Allows Region A                                                                                                                      |

|  |                                                                                                                |                                                                                                                   |
|--|----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
|  | securely expose federation endpoints to exchange SPIFFE bundles containing public key material <sup>49</sup> . | to cryptographically verify an agent's identity minted by Provider B without sharing root secrets <sup>50</sup> . |
|--|----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|

## 7.2 Zero-Trust Credential Brokerage

When an ephemeral worker spins up in a regional sandbox, a local SPIRE agent performs workload attestation (verifying the Kubernetes Service Account or Cloud Instance ID) and dynamically injects a short-lived x.509 SPIFFE Verifiable Identity Document (SVID) directly into the worker's memory<sup>51</sup>.

This identity is inherently tied to the worker's regional trust domain. If an attacker compromises a specific regional credential broker, the blast radius is mathematically contained to that specific cell's trust domain. The attacker cannot forge identities for other regions because the private keys for those intermediate CAs are physically isolated<sup>48</sup>. When the worker interacts with internal databases or external tool proxies, it presents its SVID, enabling mutual TLS (mTLS) authentication and fine-grained, policy-as-code authorization without ever relying on static passwords or long-lived API tokens<sup>47</sup>.

# 8. Multi-Region Observability and Causal Tracing

A distributed active-active system is operationally blind without a cohesive observability strategy. Reconstructing the causal sequence of an agent's actions across asynchronous regional partitions requires structured telemetry.

The platform implements OpenTelemetry messaging semantic conventions to achieve distributed context propagation<sup>53</sup>. When a workflow initiates, the system generates a globally unique Trace ID. As messages move through Kafka topics or cross regional HTTP boundaries, the context (Trace ID and Span ID) is serialized and injected into the message payload via W3C standard traceparent and tracestate headers<sup>54</sup>.

When a consumer worker in a failover region finally processes the queued message—even hours after the original region failed—it extracts the traceparent header. This allows the telemetry backend to link the new CONSUMER span directly to the original PRODUCER span<sup>57</sup>. Consequently, operators can visualize the exact bitemporal flow of an external completion claim, identifying precisely where latency spiked or where a task ownership handoff occurred across the global topology.

## 9. Failure Experiments, Chaos Engineering, and SLOs

Architectural theory must be relentlessly validated against adversarial reality. The platform's expansion follows strict, measurable evidence generated through continuous Chaos Engineering.

### 9.1 Validating Resilience with LitmusChaos

Using frameworks like LitmusChaos, operators programmatically inject turbulence into the Kubernetes clusters hosting the regional cells<sup>59</sup>. Chaos experiments are defined declaratively via Custom Resource Definitions (CRDs) and executed by a Chaos Operator<sup>59</sup>.

Crucial fault-injection scenarios include:

- **Targeted Network Partitions (pod-network-latency):** Traffic control (tc) rules via the pumba library are utilized to inject severe egress delays (e.g., 60,000ms latency) between the regional cell and the global directory<sup>61</sup>. This experiment proves whether the cell correctly falls back to its policy cache and maintains localized execution throughput without catastrophic thread starvation.
- **Infrastructure Hogging:** Utilizing tools like stress-ng to simulate CPU/Memory exhaustion, ensuring that regional schedulers correctly evict lower-priority stochastic agent tasks in favor of core control-plane components<sup>63</sup>.
- **Failover Simulation:** Completely severing ingress routing to force Global Accelerator to route traffic to the secondary region. This verifies that fencing tokens correctly reject stale writes from the partitioned primary region once connectivity is restored.

## 9.2 Measuring Success: SLIs, SLOs, and Error Budgets

The platform's reliability is governed by strict Service Level Objectives (SLOs). A Service Level Indicator (SLI) measures real-time performance (e.g., the percentage of successfully fenced cross-region handoffs), while the SLO defines the target threshold<sup>64</sup>.

For standard task execution, a 99.9% ("three nines") availability SLA allows for a maximum of 43 minutes and 12 seconds of downtime per 30-day month, or 8 hours and 45 minutes annually<sup>64</sup>. However, for the critical global directory and regional policy controllers, the target is 99.99% ("four nines"), which permits a mere 52 minutes and 34 seconds of downtime per year (approximately 4.38 minutes per month)<sup>66</sup>.

This allowed downtime is quantified as an "error budget." When chaos experiments or genuine outages burn through the error budget, automated deployment gates halt new feature releases. At the four-nines threshold, human intervention during an outage is a mathematical impossibility; the detection, traffic rerouting, and workflow continuation processes must execute entirely autonomously<sup>68</sup>.

## 10. Deliverables, Exit Criteria, and Conclusion

The establishment of a multi-region active-active agent platform necessitates abandoning legacy disaster recovery paradigms in favor of deterministic simultaneous authority. By organizing into sovereign regional cells, implementing hierarchical quota leasing, and enforcing state boundaries through monotonic fencing and idempotency, the platform achieves extreme resilience without compromising the absolute authority of its internal state.

The success of this architectural expansion is bound by the fulfillment of specific exit criteria:

- **Split-Brain Elimination:** The loss of one region or a prolonged garbage collection pause cannot cause two valid task owners; monotonic fencing tokens enforced at the data store level mathematically preclude this.

- **Idempotent External Action:** Completed external side effects cannot be repeated after a failover, guaranteed by the atomic transactional outbox pattern.
- **Sovereign Compliance:** Project residency constraints remain rigidly enforced during outages; a failure of compliant zones results in a "fail closed" state, ensuring GDPR adherence.
- **Degraded Autonomy:** Regional cells continue safe, localized workflow execution during global-service impairment by relying on cached, cryptographically signed policies.
- **Empirical Verification:** Failover, fallback, and containment protocols can be repeatedly demonstrated under automated fault injection via chaos engineering frameworks.

By treating stochastic agents as untrusted entities and wrapping their execution in these uncompromising, cryptographically verifiable architectural boundaries, the platform ensures that unprecedented scale and autonomy remain permanently tethered to human governance and deterministic safety.

## Works cited

1. How Prompt Injection Attacks Compromise AI Agents in 2026 - Atlan, <https://atlan.com/know/prompt-injection-attacks-ai-agents/>
2. CASPaxos: Replicated State Machines without logs - arXiv, <https://arxiv.org/pdf/1802.07000>
3. WPaxos: Ruling the Archipelago with Fast Consensus - University at Buffalo, <https://cse.buffalo.edu/tech-reports/2017-03.pdf>
4. Multileader WAN Paxos: Ruling the Archipelago with Fast Consensus - ResearchGate, [https://www.researchgate.net/publication/315668453\\_Multileader\\_WAN\\_Paxos\\_Ruling\\_the\\_Archipelago\\_with\\_Fast\\_Consensus](https://www.researchgate.net/publication/315668453_Multileader_WAN_Paxos_Ruling_the_Archipelago_with_Fast_Consensus)
5. Mastering Multi-Leader Replication: Topologies & Conflicts Scenarios Explained - Medium, <https://medium.com/@satyavarssheni/mastering-multi-leader-replication-topologies-conflicts-scenarios-explained-0fedf8f5ed7d>
6. Transactions - CockroachDB, <https://www.cockroachlabs.com/docs/v26.2/transactions>
7. Developer Basics - CockroachDB, <https://www.cockroachlabs.com/docs/stable/developer-basics>
8. Lease Pattern in Distributed Systems Explained - Ajit Singh, <https://singhajit.com/distributed-systems/lease/>
9. Distributed Locks: Redlock, Fencing Tokens & Advisory - AppScale Blog, <https://appscale.blog/en/blog/distributed-locks-redlock-fencing-tokens-postgres-advisory-2026>
10. Hybrid Logical Clock in Distributed Systems - Ajit Singh, <https://singhajit.com/distributed-systems/hybrid-clock/>
11. [2407.00069] Tracing Distributed Algorithms Using Replay Clocks - arXiv, <https://arxiv.org/abs/2407.00069>
12. Idempotency Patterns: Building Retry-Safe Distributed Systems - BackendBytes, <https://backendbytes.com/articles/idempotency-patterns-distributed-systems/>

13. Spanner, TrueTime & The CAP Theorem - Google Research,  
<https://research.google.com/pubs/archive/45855.pdf>
14. Sending Amazon SNS messages to an Amazon SQS queue or AWS Lambda function in a different Region - AWS Documentation,  
<https://docs.aws.amazon.com/sns/latest/dg/sns-cross-region-delivery.html>
15. Multi Region Architecture on AWS for SNS notifications - Stack Overflow,  
<https://stackoverflow.com/questions/53095645/multi-region-architecture-on-aws-for-sns-notifications>
16. GDPR Article 44 - Imperva,  
<https://www.imperva.com/learn/data-security/gdpr-article-44/>
17. Cross-Border Data Transfer Impact Assessment Under GDPR Articles 44-49: Technical Implementation Guide for Data Controllers | The Art of Service,  
<https://theartofservice.com/blog/cross-border-data-transfer-impact-assessment-under-gdpr-articles-44-49/>
18. International GDPR Data Transfers - GDPR Regulation,  
<https://www.gdprregulation.eu/international-gdpr-data-transfers/>
19. GDPR Data Transfer Rules 2026: SCC, BCR, Adequacy Decision Tree - Legiscope,  
<https://www.legiscope.com/blog/cross-border-data-transfers.html>
20. Distributed Locks with Redis | Docs,  
<https://redis.io/docs/latest/develop/clients/patterns/distributed-locks/>
21. unsafe at any time. tl;dr redlock is ok for advisory locks... | by alisdair sullivan - Medium,  
<https://medium.com/@talentdeficit/redlock-unsafe-at-any-time-40ceac109dbb>
22. How to do distributed locking - Martin Kleppmann,  
<https://martin.kleppmann.com/2016/02/08/how-to-do-distributed-locking.html>
23. Beyond the Lock: Why Fencing Tokens Are Essential - Level Up Coding,  
<https://levelup.gitconnected.com/beyond-the-lock-why-fencing-tokens-are-essential-5be0857d5a6a>
24. How to do distributed locking — Martin Kleppmann's blog - Computer Sciences User Pages,  
<https://pages.cs.wisc.edu/~remzi/Courses/739/Papers/leases-redis-problem.pdf>
25. Distributed Locks and Leases - Meridian Space,  
[https://rustycloud.org/distributed\\_systems\\_track/module-05-coordination/lesson-01-distributed-locks-leases.html](https://rustycloud.org/distributed_systems_track/module-05-coordination/lesson-01-distributed-locks-leases.html)
26. Idempotency | System Design - AlgoMaster.io,  
<https://algomaster.io/learn/system-design/idempotency>
27. Idempotency in Distributed Systems: Design Patterns Beyond 'Retry Safely' | Alok,  
<https://aloknecessary.github.io/blogs/idempotency-distributed-systems/>
28. Handling Write Conflicts in Multi-Leader Replication - Substack,  
<https://apoorvashettigar.substack.com/p/handling-write-conflicts-in-multi>
29. Multi-Cluster Replication | Temporal Platform Documentation,  
<https://docs.temporal.io/temporal-service/multi-cluster-replication>
30. Self-hosted Multi-Cluster Replication | Temporal Platform Documentation,  
<https://docs.temporal.io/self-hosted-guide/multi-cluster-replication>
31. Continue-As-New | Temporal Platform Documentation,

- <https://docs.temporal.io/workflow-execution/continue-as-new>
32. Temporal Burned Me in Production. Here's Everything I Learned About Scaling It Right | by Naman Gupta | Javarevisited - Medium,  
<https://medium.com/javarevisited/temporal-burned-me-in-production-heres-everything-i-learned-about-scaling-it-right-0fca63c35770>
  33. Manual migration | Temporal Platform Documentation,  
<https://docs.temporal.io/cloud/migrate/manual>
  34. Spanner: TrueTime and external consistency - Google Cloud Documentation,  
<https://docs.cloud.google.com/spanner/docs/true-time-external-consistency>
  35. TrueTime and external consistency | Spanner Omni - Google Cloud Documentation,  
<https://docs.cloud.google.com/spanner-omni/true-time-external-consistency>
  36. Transaction Layer - CockroachDB,  
<https://www.cockroachlabs.com/docs/v26.2/architecture/transaction-layer>
  37. Read Committed Transactions - CockroachDB,  
<https://www.cockroachlabs.com/docs/v25.2/read-committed>
  38. Measuring Latencies Between AWS Availability Zones - Bits and Cloud,  
<https://www.bitsand.cloud/posts/cross-az-latencies>
  39. AWS Latency Monitoring, <https://www.cloudping.co/>
  40. Looking at AWS Inter-Region Latency Through "Distance" - DEV Community,  
<https://dev.to/aws-builders/looking-at-aws-inter-region-latency-through-distance-34eh>
  41. Designing Scalable Rate Limiting Systems: Algorithms, Architecture, and Distributed Solutions - arXiv, <https://arxiv.org/html/2602.11741v1>
  42. AWS Global Accelerator FAQs - Amazon Web Services,  
<https://aws.amazon.com/global-accelerator/faqs/>
  43. AWS Global Accelerator: Enhancing Network Performance at a Global Scale - CloudOptimo,  
<https://www.cloudoptimo.com/blog/aws-global-accelerator-enhancing-network-performance-at-a-global-scale/>
  44. How to improve failover speed for AWS Global Accelerator or Route53 Latency routing?,  
<https://stackoverflow.com/questions/62638339/how-to-improve-failover-speed-for-aws-global-accelerator-or-route53-latency-routing>
  45. Ensure health check access for your accelerator - AWS Documentation,  
<https://docs.aws.amazon.com/global-accelerator/latest/dg/about-endpoint-groups-health-check-options.html>
  46. Best Practices for Configuring Health Checks in AWS Global Accelerator - EverLive.net,  
<https://www.everlive.net/knowledge-base/25-global/354751-what-are-the-best-practices-for-configuring-health-checks-in-global-accelerator>
  47. Implement SPIFFE/SPIRE authorization on Amazon EKS | Containers - AWS,  
<https://aws.amazon.com/blogs/containers/implement-spiFFE-spiRE-authorization-on-amazon-eks/>
  48. Scaling SPIRE | SPIFFE, [https://spiffe.io/docs/latest/planning/scaling\\_spiRE/](https://spiffe.io/docs/latest/planning/scaling_spiRE/)

49. SPIFFE/SPIRE Federation on Kind clusters - Outshift | Cisco,  
<https://outshift.cisco.com/blog/in-depth-tech/spire-federation-kind>
50. SPIFFE Federation, [https://spiffe.io/docs/latest/spiffe-specs/spiffe\\_federation/](https://spiffe.io/docs/latest/spiffe-specs/spiffe_federation/)
51. SPIFFE and SPIRE Explained: The Foundation of Zero Trust for Machines (Part 1),  
<https://blog.ogwilliam.com/post/spiffe-spire-explained>
52. Modernizing Database Authentication: CockroachDB Embraces Zero Trust with SPIFFE and SPIRE Support,  
<https://www.cockroachlabs.com/blog/zero-trust-database-authentication-spiffe-spire/>
53. oteps/text/trace/0220-messaging-semantic-conventions-span-structure.md at main - GitHub,  
<https://github.com/open-telemetry/oteps/blob/main/text/trace/0220-messaging-semantic-conventions-span-structure.md>
54. Context propagation - OpenTelemetry,  
<https://opentelemetry.io/docs/concepts/context-propagation/>
55. How to Propagate Trace Context Across Kafka Producers and Consumers - OneUptime,  
<https://oneuptime.com/blog/post/2026-02-06-propagate-trace-context-kafka-producers-consumers/view>
56. Kafka with OpenTelemetry: Distributed Tracing Guide - Last9,  
<https://last9.io/blog/kafka-with-opentelemetry/>
57. OpenTelemetry Spans and Events Explained (2026) - Last9,  
<https://last9.io/blog/opentelemetry-spans-events/>
58. OpenTelemetry Semantic Conventions: An Explainer - Dash0,  
<https://www.dash0.com/knowledge/otel-semantic-conventions-explainer>
59. Chaos Engineering With LitmusChaos - Red Hat,  
<https://www.redhat.com/en/blog/chaos-engineering-with-litmuschaos>
60. Chaos Engineering with LitmusChaos on Amazon EKS | Containers,  
<https://aws.amazon.com/blogs/containers/chaos-engineering-with-litmuschaos-on-amazon-eks/>
61. Pod network latency | Harness Developer Hub,  
<https://developer.harness.io/docs/chaos-engineering/faults/chaos-faults/kubernetes/pod/pod-network-latency>
62. Pod Network Latency Experiment Details - Litmus Docs,  
<https://litmus-docs-411023.netlify.app/docs/pod-network-latency>
63. Building Resilience with Chaos Engineering and Litmus - InfraCloud,  
<https://www.infracloud.io/blogs/building-resilience-chaos-engineering-litmus/>
64. Uptime / SLA Calculator - Downtime per 99.9% - CtrlOps,  
<https://ctrlops.io/tools/uptime-sla-calculator>
65. SLA Uptime Calculator - Fivenines, <https://fivenines.io/tools/sla-uptime-calculator>
66. Three Nines (99.9%) Uptime - SLA & Downtime calculator - Hyperping,  
<https://hyperping.com/three-nines>
67. SLA and Uptime Calculator - Ajit Singh, <https://singhajit.com/tools/sla-calculator/>
68. 99.99% Uptime SLA: How Much Downtime Per Year? - Hyperping,  
<https://hyperping.com/99.99>